



NOTES:

1. INLET: 1/4" FLARE FOR 6' HOSE WITH CO2 TANK CONNECTION
2. OUTLES: 5/16" BARB SHUTOFFS W/CHECK
3. GAUGES: 60# (3 EA) AND 2000#
4. SAFETY BLOWOFF: 60 ± 5 PSI
5. WORKING PRESSURE: 0-50 PSI
6. POLY BONNETS WITH ADJ. RED CAPS

| | | |
|---|-------------------------------------|--------------|
| MATERIAL | NAME | DATE |
| | DRAWN | JPK 02/29/12 |
| FINISH | ENG APPR. | |
| | PROPRIETARY AND CONFIDENTIAL | |
| DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2" BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005 | | |
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED. | | |



TITLE:
REG, PRI, BEER, 3P3P, 60#, 6' HOSE W/CO2, 5/16B-CV SHUTOFF, 2000#, RED, WALL MNT

| | | |
|----------|------------------|----------|
| SIZE | DWG. NO. | REV |
| A | T762WMHP-6_SALES | A |

SCALE: 1:2 DO NOT SCALE DRAWING SHEET 1 OF 1